



H-D[®] BILLIARD LAMP INSTRUCTIONS

WARNING: To avoid risk of electrical shock, turn off power while installing or servicing. We strongly recommend that a qualified electrician install this fixture.

Hanging Instructions

1. Turn OFF power.
2. Carefully unpack and place all parts on a soft surface.
3. Take threaded pipe from parts bag place bracket on threaded pipe, secure with hex nut.
4. Place second hex nut on threaded pipe add mounting strap. Threaded pipe must extrude from top of mounting strap, secure with third hex nut.
5. Connect mounting strap to outlet box with screws.
6. Place nipples through bracket secure with washers and nut.
7. Run wires through canopy and threaded pipe, connect to supply wires securing with wire nuts.
8. Slip canopy over bracket, attach collar loops to each side of canopy and secure with finial. Attach chains.

Important Notes:

- Fixture wires are connected to the proper house supply wires. If you have any doubt about which house supply wire is the white and which is the black, contact a licensed electrician.
- Insure the electrical box is securely mounted and will be able to support the weight of the fixture.
- The fixture ground wire (bare/green installed wire) is NOT connected to current carrying supply wires.
- No bare wires are exposed outside the wire connectors when joining current carrying wires. The insulation on any of the wires must not be damaged during installation.
- Power is off when installing light bulbs into the fixture. Use light bulbs specified for this fixture. (No greater than 100 watts)

Warranty:

Free replacement of any part that fails within 90 days from date of purchase, excluding shipping costs. Void if damaged by misuse, accidents, alterations, failure to follow instructions, fire, flood, and acts of God.

Questions or comments, contact us at:

BrandedProducts.com

