



M7

UNIVERSAL SEAM SEALANT

For the Seaming of Mohawk Resilient Vinyl Flooring Products

- Very quick, strong bond development, dries clear.
- Low odor. Does not contain ammonia or solvents.
- Water clean up when wet. Water resistant when dry.
- CRI Green Label Plus Approved
- FloorScore® certified
- Passes water penetration test at 10,000+ cycles on prepared seams

Mohawk M7 Universal Seam Sealant is a strong, solvent-free adhesive with superior bond and tensile strength when dry. It does not contain ammonia, is non-flammable, and dries to a clear film that is highly water resistant. Mohawk M7 has low odor and “zero” (calculated) VOC, which makes it ideal for use in schools, public buildings and other areas where odor is a concern.

Applications:

- Vinyl sheet goods – high performance and durable seam adhesive for commercial and residential installations

Coverage:

Approximately 400 linear feet per 32 ounces using 1/8” bead

Shelf Life:

1 year from manufacturing date in an unopened container

Directions for Use:

1. Prepare the floor covering according to the manufacturer’s instructions.
2. Apply continuous bead of seam sealer along the edge of the backing on the first piece of vinyl.
3. Immediately place the edge of the second piece of floor covering into contact with the first piece which has the seam sealer on it. To achieve a good bond, it is essential for the two pieces to have a tight fit, and traffic on the seamed area should be restricted for at least 24 hours.
4. Sheet goods will require clean wipe along seams while adhesive is still wet.



**Available in 1 US Quart
Mohawk Style M7**



5. Clean any smears of seam sealer or adhesive with water while material is in the wet state. Dried residues may require the use of an adhesive remover.

This product is considered non-hazardous. VOC compliant with CA SCAQMD Rule 1168. All components of this product appear on the Inventory of Chemical Substances published by the U.S. Environmental Protection Agency (EPA) under the authority of the Toxic Substances Control Act (TSCA).

In case of eye contact, flush with water for 10-15 minutes. If irritation persists contact a physician. Prolonged skin contact may cause slight irritation, wash with soap and water. If swallowed, consult a physician. Avoid excessive heat or cold, protect from freezing. Store indoors at a temperature of 65°-85°F. Safety glasses and gloves are recommended if contact is necessary. DOT Hazard Class: Unregulated.

24-Hour Emergency in the USA:
Chemtrec 1-800-424-9300