

## **Audio Coupling** Miniature Encapsulated Transformer

# **MET-09-T**

#### **Description:**

Triad's high reliability audio transformers provide the durability and precision required in today's demanding designs. These transformers are available for a wide variety of applications.

### Electrical Specifications (@20C)

Power	Matching Impedance		Max. Ma DC	DC Resistance (Ω)		Overall
level	Primary	Secondary	Unbalance in Primary	Primary	Secondary	Turns
(mW)						Ratio
40	10KΩ CT	10KΩ CT	1.0	1000	1300	1.0:1.0

Operating Temperature: -20C° to 85C°

Storage Temperature: -55C° to 105C°

Frequency Response: + 2.0 dB, at 300 Hz to 100K Hz (1 KHz Ref.)


Longitudinal Balance: 60dB Min @ 1 KHz

\*Max power at 300Hz

Pri-Sec Hipot test (Pri-Sec): 1000 VRMS for 1 sec.

#### **Construction:**

Plug-in terminals are precision spaced to provide fixed mounting centers. Epoxy molded case includes a .020" recess for ease of solder inspection. Leads are Tin plated 0.020" in diameter.




RoHS Compliance: As of manufacturing date February 2005, all standard products meet the requirements of 2011/65/EU, known as the RoHS initiative.

\*Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics website for the most current version. For soldering and washing information please see http://www.triadmagnetics.com/fag.html

	460 Harley Knox Blvd. Perris, California 92571	Publish Date: Septe
--	---	---------------------





tember 22, 2017