



Playa Bella 5.5mm EWC LVT

Specification

| | |
|-----------------|--|
| Product: | Extruded Waterproof Core Luxury Vinyl Plank and Tile |
| Construction: | 1.5mm virgin PVC top layer 4.0mm waterproof core (virgin PVC, stone powder) |
| Top Wear layer: | 8mil (0.2mm) with Ceramic bead and UV coating |
| Finish: | Textured finish, square edges |
| Locking system: | 4-sided licensed Unilin angle-tap |
| Installation: | Float, Glue Down |
| Packaging: | 5.5mm x 5 7/8" x 48" plank 12 planks/carton 23.32 sf/carton 60 cartons/pallet 1399.2 sf/pallet 20 pallets/container |
| Warranty: | 15 year residential 5 year light commercial |

Performance Specification:

| | | |
|--------------------------------|----------------|---|
| Density | ASTM D6111-13a | >0.8g/cm ³ |
| Static Coefficient of Friction | ASTM 1028-07 | 0.68 slip, passes ADA/OSHA requirements |
| Chemical Resistance | ASTM F925-13 | Pass |
| Heat Resistance | ASTM F1514-03 | meets <8.0 Delta E requirement |
| Light Resistance | ASTM F1515-003 | meets <8.0 Delta E requirement |
| Thickness Swell | ASTM D7519-11 | Class 4, Heavy Commercial |
| Dimensional Stability | ASTM 2199-09 | Passes |

| | |
|------------------------|---------------------------------------|
| Certifications: | CARB Compliant FLOORSORE Certified |
|------------------------|---------------------------------------|