

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :	
Model #:	
Item #:	Qty:
Available W/H :	
Approval :	

# **Undercounter Refrigerator**

Side Mount Undercounters

J Series

**Model: JUR-36** 



## \_\_\_ FEATURES & BENEFITS =\_\_

### ■ Hot gas condensate system Only Turbo Air models

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

#### ■ Side mount compressor unit

By positioning the compressor on the side of the unit, refrigerators can now be serviced without being moved. Our innovative, front breathing feature also allows this model to provide high efficiency in narrow spaces.

#### Efficient refrigeration system

Turbo Air J series refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

#### Exterior & interior of the cabinet

The Turbo Air J series boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides, back and AL door liners. It guarantees the utmost in cleanliness and long product life. It can add a touch of style to the most refined setting.

## ■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

### ■ Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

### ■ Magnetic door gaskets

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

- Adjustable, heavy duty, PE (polyethylene) coated wire shelves
- Refrigerator holds 33°F ~ 39°F for the best in food preservation











JUR-36	1	6.37	1	1/4	4.5	190	353/8 x 271/2 x 283/4
Model	Swing Door	CU./FT.	#of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D*x H <sup>†</sup> (inches)

(unit: inch)

# Undercounter Refrigerator

# **Model: JUR-36**

ELECTRICAL DATA	LECTRICAL DATA				
Voltage	115/60/1				
Plug Type	① NEMA 5-15P				
Full Load Amperes	4.5				
Compressor HP	1/4				
Cord Length (ft.)	9.2				
Refrigerant	R-134A				
DIMENSIONAL DATA	MENSIONAL DATA				
Net Capacity (cu. ft.)	6.37				
Ext. Length Overall (in.)	353/8 (899mm)				
Ext. Depth Overall (in.) *	27 <sub>1/2</sub> (699mm)				
Ext. Height Overall (in.)†	283/4 (730mm)				
# of Doors	1				
# of Shelves	1				
Net Weight (lbs.)	157				
Gross Weight (lbs.)	190				
Shelf Size (in.)	191/2 x 201/2				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

† Height does not include 5" for caster height.


# 2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor

- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- 2.5" caster available (optional)
- Legs available (optional)


#### ■ OPTIONAL ACCESSORIES :

- ☐ 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- ☐ 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- ☐ 6" ABS plastic leg: 30221M0200
- ☐ 6" stainless steel leg: 30221M0600
- ☐ Additional PE coated wire shelf: KR99000100
- Door lock: extra lead time will apply, please call factory for more details to order


# **PLAN VIEW**



**PLAN VIEW** 



**FRONT VIEW** 



SIDE VIEW

■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002

Ver.201701



















<sup>\*</sup> Depth does not include 1" for rear spacers.