

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Drainat	
Project	
·	

Model # : Item # :

Available W/H :

Approval :

Half Solid Door Refrigerator

FEATURES & BENEFITS Self-cleaning condenser device Only at Turbo Air

The accumulation of dust in the condenser causes the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products in refrigerators. The self-cleaning condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Digital temperature control & monitor system

- Keep food products safe by maintaining constant temperatures.
- Alarms that sound when doors are not sealed shut; protect against food spoilage that originate from cold air leaks.
- Digital display allows for easy monitoring.
- Programs interpret the condition of refrigeration systems by self-diagnosis.
- Automatic evaporator fan motor delays.

All stainless steel cabinet construction

The Turbo Air Pro model boasts all stainless steel interior and exterior (galvanized steel top, bottom and back). It guarantees the utmost in cleanliness and long product life. The Pro model can add a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving Only Turbo Air models

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Pro Series uniquely provides stainless steel shelving.

Hot gas condensate system Only Turbo Air models

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but thoroughly prevents the overflow of condensate water.

Cold air distribution system

Door pressure release device

Efficient refrigeration system

Pro Series's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

CU./FT.

25

#of

Shelves

3

HP

1/3

High-density polyurethane insulation The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- LED interior lighting
- Top mount compressor

Swing

Door

2





Refrigerator holds 33°F ~ 38°F for the best in food preservation

AMPS	Crated Weight (Ibs.)	$L \ge D^* \ge H^{\dagger}$ (inches)		
5.2	356	283/4 x 337/8 x 78		

Model

PRO-26-2R

* Depth does not include 1-1/8" for door handles. † Height does not include 5" for caster height.

Reach-In Top Mount Pro Series

Qty :

Model : PRO-26-2R

Half Solid Door Refrigerator

Model : PRO-26-2R

ELECTRICAL DATA		
Voltage	115/60/1	
Plug Type	NEMA 5-15P	
Full Load Amperes	5.2	
Compressor HP	1/3	
Feed Wires with Ground	3	
Cord Length (ft.)	9	
Refrigerant	R-134A	
DIMENSIONAL DATA		
# of Doors	2	
# of Racks Accepted	1	
Net Capacity (cu. ft.)	25	
Ext. Length Overall (in.)	283/4 (730mm)	
Ext. Depth Overall (in.)*	337/8 (860mm)	
Ext. Height Overall (in.) [†]	78 (1981mm)	
Int. Length Overall (in.)	243/4 (630mm)	
Int. Depth Overall (in.)	291/2 (750mm)	
Int. Height Overall (in.)	583/4 (1493mm)	
Net Weight (lbs.)	315	
Gross Weight (lbs.)	356	
# of Shelves	3	
Shelf Size (L x D) (in.)	233/4 x 251/4	

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection. * Depth does not include 1-1/8" for door handles.

Depth does not include 1-1/8" for door handle
Height does not include 5" for caster height.

• WARRANTY : 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor

- Door locks standard
- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Easy replaceable one piece magnetic door gaskets
- Solid and sturdy grille design
- Legs available (optional)
- Half size pan racks available (optional)

OPTIONAL ACCESSORIES :

- 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- G" stainless steel leg: 30221M0600
- □ Additional stainless steel shelf: SP2F180100
- □ Half door bun tray rack: TSP-2224 (each holds up to six 18"L x 26"D sheet pans- sold separately)

3 YEAR


5 YEAR WARRANTY


(GERMAN

KNIFE



(unit : inch)





SIDE VIEW

Ver.201608

Turbo Air : 800-627-0032
GK : 800-500-3519
Warranty : 800-381-7770
AC : 888-900-1002

GREEN WORLD Turbo air

Turbo air

Intertek ISO9001:2008

CQC

(E]l

US