

TRUE FOOD SERVICE EQUIPMENT, INC.

2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 Fax (636)272-2408 • Toll Free (800)325-6152 • Intl Fax# (001)636-272-7546 Parts Dept. (800)424-TRUE • Parts Dept. Fax# (636)272-9471 • www.truemfg.com

| Project Name: | AIA# |
|---------------|-------|
| Location: | |
| Item #: Qty: | SIS # |
| Model #: | |

Model:

GDM-23F-HC-LD

Glass Door Merchandiser:

Swing Door Freezer with Hydrocarbon Refrigerant and LED Lighting



GDM-23F-HC-LD

- The world's #1 manufacturer of glass door merchandisers.
- Designed using the highest quality materials and components to provide the user with an attractive, point of purchase merchandiser that brilliantly displays frozen food and ice cream, resulting in high impulse sales.
- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydro carbon refrigerant that has zero (0) ozone depletion potential (ODP), & three (3) global warming potential (GWP).
- Oversized, factory balanced, refrigeration system holds -10°F (-23.3°C). Ideal for ice cream and frozen food products.
- Exterior non-peel or chip white laminated vinyl; durable and permanent.
- Interior attractive, NSF approved, white aluminum interior liner with stainless steel floor.
- Self closing door. Positive seal, torsion type closure system.
- Triple pane thermal glass door assembly with extruded aluminum frame.
- LED interior lighting provides more even lighting throughout the cabinet. Safety shielded.
- Entire cabinet structure is foamed-inplace using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).

Bottom mounted units feature

- "No stoop" lower shelf to maximize product visibility.
- Easily accessible condenser coil for cleaning.

ROUGH-IN DATA

Specifications subject to change without notice. Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

| | | | Cabinet Dimensions (inches) (mm) | | | | | NEMA | Cord Length (total ft.) | Crated Weight (lbs.) | |
|---------------|-------|---------|--|-----|------|-----|----------|------|-------------------------------|----------------------------|------|
| Model | Doors | Shelves | W | D† | Н | HP | Voltage | Amps | | (| (kg) |
| GDM-23F-HC-LD | 1 | 4 | 27 | 29% | 78% | 1 | 115/60/1 | 9.3 | 5-15P | 9 | 350 |
| | | | 686 | 759 | 1998 | N/A | | N/A | A | 2.74 | 159 |

† Depth does not include 11/8" (29 mm) for door handle.

▲ Plug type varies by country.



GDM-23F-HC-LD

Glass Door Merchandiser:

Swing Door Freezer with Hydrocarbon Refrigerant and LED Lighting



STANDARD FEATURES

DESIGN

- True's glass door freezers are designed with enduring quality that protects your long term investment.
- True's commitment to using the highest quality materials and oversized refrigeration systems provides the user with colder product temperatures, and lower utility costs in an attractive merchandiser that brilliantly displays frozen food and ice cream.

REFRIGERATION SYSTEM

- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), & three (3) global warming potential (GWP).
- High capacity, factory balanced refrigeration system that maintains -10°F (-23.3°C) temperatures. Ideal for both frozen foods and ice cream.
- State of the art, electronically commutated evaporator and condenser fan motors. ECM motors operate at higher peak efficiencies and move a more consistent volume of air which produces less heat, reduces energy consumption and provides greater motor reliability.
- Bottom mounted condensing unit positioned for easy maintenance. "No stoop" lower shelf maximizes visibility by raising merchandised product to higher level.
- Automatic defrost system time-initiated, temperature-terminated. Saves energy consumption and provides shortest possible defrost cycle.

CABINET CONSTRUCTION

- Exterior non-peel or chip white laminated vinyl; durable and permanent.
- Interior attractive, NSF approved, white aluminum liner with stainless steel floor.
- Insulation entire cabinet structure is foamedin-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- Welded, heavy duty steel frame rail, black powder coated for corrosion protection.
- Frame rail fitted with leg levelers.
- Illuminated exterior sign panel. Variety of sign options available.

DOOR

- Triple pane thermal insulated glass door assembly with extruded aluminum frame.
- Door fitted with 12" (305 mm) long extruded handle.
- Self closing door. Positive seal, torsion type closure system.
- Magnetic door gaskets of one piece construction, removable without tools for ease of cleaning.

SHELVING

- Four (4) adjustable, heavy duty PVC coated wire shelves 22% "L x 21 ¼"D (582 mm x 540 mm). Four (4) chrome plated shelf clips included per shelf.
- Shelf support pilasters made of same material as cabinet interior; shelves are adjustable on ½"(13 mm) increments.

LIGHTING

 LED interior lighting provides more even lighting throughout the cabinet. Safety shielded.

MODEL FEATURES

- Evaporator is epoxy coated to eliminate the potential of corrosion.
- See our website www.truemfg.com for latest color and sign offerings.
- Backguard and floor rack ensure optimum airflow.
- Listed under NSF-7 for the storage and/or display of packaged or bottled product.

ELECTRICAL

 Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.





OPTIONAL FEATURES/ACCESSORIES

Upcharge and lead times may apply.

- ☐ Black exterior.
- ☐ Stainless exterior.
- ☐ Black aluminum interior liner with black shelving.
- ☐ Stainless interior liner.
- \square 6" (153 mm) standard legs.
- \square 6" (153 mm) seismic/flanged legs.
- ☐ 2½" (64 mm) diameter castors.
- ☐ 4" (102 mm) diameter castors.
- ☐ Novelty baskets.
- ☐ Pricing strips.

PLAN VIEW





PLAN VIEW

WARRANTY*

Three year warranty on all parts and labor and an additional 2 year warranty on compressor. (U.S.A. only)

*RESIDENTIAL APPLICATIONS: TRUE assumes no liability for parts or labor coverage for component failure or other damages resulting from installation in non-commercial or residential applications.

METRIC DIMENSIONS ROUNDED UP TO THE NEAREST WHOLE MILLIMETER

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

| Model | Elevat | tion Right | Plan | 3D | Back |
|---------|------------|------------|-----------|---------|------|
| GDM-23F | HC-LD TFAZ | TFAY03 | S TFAZ03F | TFAZ033 | |

TRUE FOOD SERVICE EQUIPMENT