

# 2045 Montreux Plus


Jan 31, 2013



## ZipperLock® Technology

Real world experience shows that high tuft bind alone is not sufficient to prevent zippering. ZipperLock® Technology includes the following:

- Dual Bonding provides excellent lamination strength and tuft bind
- Interlocking Tuft Placement prevents unraveling




## Stain Proof - No Exceptions™

Strudon® is inherently stain proof. Carpets made of Strudon® fiber are ideal for high stain environments including food service areas and rental units.




## Scoured & Extracted™ to Stay Clean Longer

This solution dyed carpet is Scoured & Extracted™ to remove the processing oils that attract soil. Scouring makes the carpet easier to clean, and helps prevent accelerated soiling known as Rapid Resoil.



## Kraus® Endorsed Recycling Program

This product is eligible for a recycling program. 100% of this carpet is recyclable.



## Commercial Warranties

- Lifetime Stain Proof - No Exceptions™
- 10 year Commercial wear
- 10 year ZipperLock® + no edge ravel + no delamination
- 10 year Anti-Shock

See full text for details.

## Style 2045

02 Camel  
30 Sand Dune

03 Black Pepper  
37 Acorn

06 Dust Storm  
39 Coal

07 Sea Breeze  
48 Fir

April 28, 2011

Style  
Manufacturer

2045 Montreux Plus  
Kraus®

## CONSTRUCTION

Fiber system	92% BCF Strudon® / 8% BCF nylon	
Construction	Interlocking level loop	
Standard backing system	ZipperLock® dual bonding	
Pile weight	20 oz/y <sup>2</sup>	678 g/m <sup>2</sup>
Pile height	0.18"	4.5 mm
Gauge	1/10	39.4 rows/10 cm
Stitches	9.7 s.p.i.	38.2 stitches/10 cm
Density	4500	8.7 kilotex/cm <sup>2</sup>

## PROTECTION

Coloration	Solution dyed / yarn dyed
Stain resistance	Stain Proof - No Exceptions™
Soil protection	Scoured & Extracted™

## SUSTAINABILITY

CRI/CCI air quality test	Green Label Plus	GLP 4678
Recycling program	Eligible for recycling program	

## PERFORMANCE

Ravel test performance	Construction prevents raveling when tested to PTL-CR (center ravel) and PTL-ER (edge ravel) protocols
Static generation	3.0 kV or less (AATCC 134)
Flammability	CGSB 4GP-129 CAN 4-S102.2 (generic per NBC supplement) Radiant Panel ASTM E648 – Class II
Colorfastness to light	5.0 (AATCC 16)

## INSTALLATION

Format	12' wide	3.66 m
Approximate pattern repeat (w x l)	5/8" x 1 1/4"	1.6 cm x 2.8 cm
Recommended adhesive	Kraus I Premium Adhesive™ KPA-302	
Installation method	Suitable for direct glue or cushion installations	
Chair protectors	Recommended for direct glue installations Mandatory for cushion installations	

## WARRANTIES

Warranties	Lifetime Stain Proof – No Exceptions™
(See full text for details)	10 year Commercial wear 10 year ZipperLock® + no edge ravel + no delamination 10 year Anti-shock

Follow manufacturer's installation recommendations. Correct seam sealing is necessary to prevent seam breakdowns. For best results, seams must be row cut and the carpet must be dry laid to optimize pattern match. Due to dye lot variations, actual material may vary slightly from samples. The manufacturer reserves the right to modify the specifications to improve the product without notice and without prejudice. See [krausflooring.com](http://krausflooring.com) for latest specifications.

E&OE.

