

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :	
Model #:	
Item #:	Qty:
Available W/H :	
Approval :	

Glass & Solid Half Door Refrigerator

Reach-In Top Mount Premiere Pro Series

Model: PRO-50R-GSH

== FEATURES & BENEFITS ==_

Digital temperature control & monitor system

- Keep food products safe by maintaining constant temperatures.
- Alarms that sound when doors are not sealed shut; protect against food spoilage that originate from cold air leaks.
- · Digital display allows for easy monitoring.
- Programs interpret the condition of refrigeration systems by self-diagnosis.
- · Automatic evaporator fan motor delays.

All stainless steel cabinet construction

The Turbo Air Premiere Pro model boasts all stainless steel interior and exterior (galvanized steel top, bottom and back). It guarantees the utmost in cleanliness and long product life. The Premiere Pro model can add a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Premiere Pro series uniquely provides stainless steel shelving.

■ Hot gas condensate system Only Turbo Air models

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but thoroughly prevents the overflow of condensate water.

- Cold air distribution system
- Door pressure release device

Efficient refrigeration system

Premiere Pro's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- LED interior lighting
- Top mount compressor
- Refrigerator holds 33°F ~ 38°F for the best in food preservation













	g :		н. С			Custad	*+
Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	L x D [*] x H [†] (inches)
PRO-50R-GSH	4	51	6	1/2	9.1	543	513/4 x 337/8 x 78

(unit: inch)

Glass & Solid Half Door Refrigerator

Model: PRO-50R-GSH

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type					
Full Load Amperes	9.1				
Compressor HP	1/2				
Feed Wires with Ground	3				
Cord Length (ft.)	9				
Refrigerant	R-134A				
DIMENSIONAL DATA					
# of Doors	4				
# of Racks Accepted	2				
Net Capacity (cu. ft.)	51				
Ext. Length Overall (in.)	51 _{3/4} (1314mm)				
Ext. Depth Overall (in.)*	337/8 (860mm)				
Ext. Height Overall (in.)†	78 (1981mm)				
Int. Length Overall (in.)	47 _{3/4} (1214mm)				
Int. Depth Overall (in.)	291/2 (750mm)				
Int. Height Overall (in.)	58 _{3/4} (1493mm)				
Net Weight (lbs.)	495				
Gross Weight (lbs.)	543				
# of Shelves	6				
Shelf Size (L x D) (in.)	23 x 251/4				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


■ WARRANTY: 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor


- Door locks standard
- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Easy replaceable one piece magnetic door gaskets
- Solid and sturdy grille design
- Legs available (optional)
- Half size pan racks available (optional)

■ OPTIONAL ACCESSORIES:

- ☐ 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- ☐ 6" stainless steel leg: 30221M0600
- ☐ Additional stainless steel shelf: SP8F180100
- ☐ Half door bun tray rack: TSP-2224 (each holds up to six 18"L x 26"D sheet pans- sold separately)

PLAN VIEW





SIDE VIEW

Ver.201603













■ Warranty: 800-381-7770 ■ AC: 888-900-1002











^{*} Depth does not include 1-1/8" for door handles.

[†] Height does not include 5" for caster height.